

## DIGITAL CLAMP METERS MS2000G / MS2000R



### Specifications

MS2000G MS2000R

Specifications	Range	Accuracy
DC Voltage	2V/20V/200V	±(0.5%+1)
	1000V	±(1.0%+2)
	400mV/4V/40V/400V/1000V	±(1.0%+2)
AC Voltage	200V/750V	±(1.0%+5)
	4V/40/400/750V	±(1.2%+3)
DC Current	400A/1000A	±(3.0+5)
	200A/2000A	±(2.0%+5)
AC Current	400A/1000A	±(3.0+5)
	200Ω/20KΩ/2MΩ	±(1.2%+2)
Resistace	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(2.0%+5)
	Frequency	0~2KHz
Temperature	0~100kHz	±(2.0%+2)
	-20°C~750°C	±(2%+2)
	-4°F~1832°F	±(2%+4)

### Features

Features		2000	4000
Display	counts	●	●
Jaw Opening	Φ55mm/2.2"	●	●
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
Data Hold		●	●
Display Backlight		●	●
True RMS	True root mean square measurement	●	●

### General

Power Supply	1×9V/6F22 Battery
Product Size	282mm×104mm×47mm/11"×4.1"×1.85"
Product Weight	503g/1.1lb
Safety Rating	CAT II 1000V RoHS

● Feature Difference

### MS2000G

JAW SIZE

Φ55mm/2.2"

VOLTAGE AC 750A  
DC 1000A

CURRENT

AC 2000A



### MS2000R

JAW SIZE

Φ55mm/2.2"

VOLTAGE AC 750A  
DC 1000A

CURRENT AC 1000A  
DC 1000A

