


PRODUCT-DETAILS

HK1-11K

HK1-11K Auxiliary Contact



General Information

Extended Product Type	HK1-11K
Product ID	1SAM201902R1201
EAN	4013614523311
Catalog Description	HK1-11K Auxiliary Contact
Long Description	HK1-11K Aux.-contact 1 NO + 1 NC with Push-In terminals

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Data Sheet, Technical Information	1SBC100212C0201
Instructions and Manuals	2CDC131120M6801 2CDC131034M6801 2CDC131022M6802

Dimensions

Product Net Width	9 mm
Product Net Height	90 mm

Product Net Depth / Length	74.5 mm
Product Net Weight	0.035 kg

Technical

Terminal Type	Push-in Spring Terminals
Rated Operational Voltage	690 V AC 600 V DC
Rated Operational Current AC-15 (I _e)	(240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A
Rated Operational Current DC-13 (I _e)	(125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0.15 A (600 V) 0.15 A
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Degree of Protection	IP20
Electrical Durability	100000 cycle
Mechanical Durability	100000 cycle
Recommended Screw Driver	M3
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts CO (SPDT)	0
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-5-1 UL 508 UL 60947-1 UL 60947-5-1
Product Name	Auxiliary Contact
Suitable For	MS116 MS132 MO132 MS165 MO165
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	Auxiliary Contact

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Contact Rating UL/CSA	B600 Q600

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -50 ... +80 °C
Resistance to Shock acc.	11 ms Pulse 25g

to IEC 60068-2-27

Certificates and Declarations (Document Number)

ABS Certificate	1SAA963001-0101
CCC Certificate	1SAA963003-3803
Declaration of Conformity - CE	1SAD938514-0125
Instructions and Manuals	2CDC131120M6801 2CDC131034M6801 2CDC131022M6802
RINA Certificate	Rina_MS132

Container Information

Package Level 1 Width	25 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	93 mm
Package Level 1 Gross Weight	0.08 kg
Package Level 1 EAN	4013614523250
Package Level 1 Units	box 2 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	0.61 kg
Package Level 2 EAN	4013614523427
Package Level 2 Units	carton 160 piece

Classifications

Object Classification Code	Q
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4742 >> Electrical contacts
E-Number (Sweden)	3110465

Categories

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories

