



A9A26927

Acti 9 -Auxiliary fault contact iSD - 1 C/O - AC/DC



Download your A9A26927 datasheet



Characteristics | Documents & Downloads

Change your selection

Discover other products & accessories



Discover your Schneider Electric tools

Main

Hide

Range	Acti 9
Product or component type	Fault contact
Device short name	ISD
Signal contacts composition	1 C/O
[In] rated current	1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC 3 A at 415 V AC - 50/60 Hz 6 A at 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Hide

Range compatibility	Acti 9 iC60 Acti 9 iDPN Vigi Acti 9 iLD Acti 9 iC60 RCBO Acti 9 iC65 Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iC40
[Ui] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	33 g
Colour	White
Connections - terminals	Screw clamp terminal 2 cable(s) 2.5 mm ² rigid Screw clamp terminal 1 cable(s) 0.5...2.5 mm ² flexible Screw clamp terminal 1 cable(s) 1...4 mm ² rigid Screw clamp terminal 2 cable(s) 1.5 mm ² flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Hide

Standards	EN/IEC 60947-5-1
-----------	------------------

IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Hide

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available  download Product environmental
Product end of life instructions	Available  download End of life manual