



## Main

|                              |                                                                              |
|------------------------------|------------------------------------------------------------------------------|
| Device short name            | Motor mechanism module with SDE adaptor                                      |
| Product or component type    | Motor mechanism                                                              |
| Device application           | Automatic spring charging                                                    |
| Range compatibility          | Compact - Compact NSX<br>Compact - Compact NSX DC<br>PowerPact Multistandard |
| Product compatibility        | PowerPact H-Frame<br>PowerPact J-Frame                                       |
| [In] rated current           | 100 A<br>160 A                                                               |
| [Uc] control circuit voltage | 208...277 V AC 60 Hz<br>220...240 V AC 50/60 Hz                              |

## Complementary

|                             |                                                                    |
|-----------------------------|--------------------------------------------------------------------|
| Control type                | Standard                                                           |
| Control signal type         | Impulse<br>Maintained                                              |
| Mounting mode               | Fixed                                                              |
| Response time               | < 600 ms - during opening time<br>< 80 ms - during closing time    |
| Maximum operating frequency | 4 per minute                                                       |
| Power consumption in VA     | <= 500 VA - during closing time<br><= 500 VA - during opening time |
| Provided equipment          | SDE adaptor                                                        |
| Locking options description | 1 to 3 padlocks Ø 5 to Ø 8<br>Padlocking in OFF position           |

## Offer Sustainability

|                          |                                                                       |
|--------------------------|-----------------------------------------------------------------------|
| Sustainable offer status | Green Premium product                                                 |
| RoHS (date code: YYWW)   | Compliant - since 1821 - Schneider Electric declaration of conformity |

|                                  |                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a> |
| Product environmental profile    | Available                                                                                                              |
| Product end of life instructions | Available                                                                                                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|